		TE	CHNICAL	. SPECIFICA	ATION	Nr:	I-ET-3010.	1Y-5121-6	00-P4	K-002	2	
BR		CLIENT	<u> </u>		R	ÚZIOS			SHEET:			21
<i>(-)</i>	Λ	JOB:				PACITY FPS	0					
PETROBRAS		AREA:					0					
		TITLE:			E	BÚZIOS						
	^ _			DOTABLE	: \//ATE	R MAKER S	EVETEM		IN	ITERI	NAL	
SR	GE					1501 A/B)	OTOTEW			ESU	P	
File No.: MICRO	OSOFT WORE) 2016 – I-E	ET-3010.1Y-5121	-600-P4X-001_A.doo	_	1301 A/D)						
				INDE	X OF RI	EVISIONS						
	I											
REV.			DI	ESCRIPTION	ON AND)/OR REV	ISED SHI	EETS				
0	ORI	GINA	L ISSUE									
Α	REV	/ISED	WHERE	E INDICAT	ED							
	<u> </u>) <u>-</u>	I prv •	DEVE	DEV. C	DEV 5	l pev e	DEV. 5	BE::	0	_	EV. 11
DATE		EV. 0	REV. A MAR/09/21	REV. B	REV. C	REV. D	REV. E	REV. F	REV	. G	R	EV. H
PROJECT		N/08/21 ENG	ENG									
EXECUTION		CXZ0	CXZ0									
CHECK		CXW3	BYA6									
APPROVAL		CYEL	CYEL						1			


THE INFORMATION CONTAINED IN THIS DOCUMENT IS PETROBRAS PROPERTY AND MAY NOT BE USED FOR PURPOSES OTHER THAN SPECIFICALLY INDICATED HEREIN.

THIS FORM IS PART OF PETROBRAS N-381 REV.J ANNEX A - FIGURE A.1.



TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	94X-002	REV.	Α
BÚZIOS		SHEET: 2	of	21
TITLE: POTABLE WATE	ER MAKER SYSTEM	INTERNA		
(UM-5121	501 A/B)	ESU	P	

TABLE OF CONTENTS PAGE INTRODUCTION4 1.1 OBJECTIVE.......4 1.3 ABBREVIATIONS......4 2. NORMATIVE REFERENCES......4 2.3 CLASS APPROVAL AND CERTIFICATION5 4. DESIGN REQUIREMENTS8 4.1 DESIGN CONDITIONS......8 4.2 SAFETY REQUIREMENTS8 5. PACKAGE SCOPE OF SUPPLY9 6. PACKAGE SPECIFICATION10 7. GENERAL REQUIREMENTS......11 8. PACKAGE MANUFACTURING14 8.1 GENERAL 14 8.2 QUALITY ASSURANCE AND CONTROL SYSTEM14



8.6	PRE-COMMISSIONING AND COMMISSIONING	17
9.	PACKAGE DELIVERY REQUIREMENTS	18
9.1	PRESERVATION, PACKING AND TRANSPORTATION	18
9.2	SPARE PARTS, CONSUMABLES AND TOOLS	20
9.3	DOCUMENTATION	20
9.4	TRAINING	21

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	REV.	
BR	BÚZIOS	3	SHEET: 4	of 21	
PETROBRAS	POTABLE WATI	ER MAKER SYSTEM	INTERNAL		
	(UM-5121	501 A/B)	ESU	Р	

1. INTRODUCTION

1.1. OBJECTIVE

The purpose of this technical specification is to describe the minimum requirements for the design, manufacturing, assembly, supply, installation, commissioning, and tests of POTABLE WATER MAKER (UM-5121501A/B) in conformance with relevant regulations and High Capacity FPSO basic design documentation.

1.2. DEFINITIONS

PACKAGE: It is defined as an assembly of equipment supplied interconnected, tested and ready to operate, requiring only the available utilities from the Unit for the Package operation.

PACKAGER: It is defined as the responsible for project, assembly, construction, fabrication, testing and furnishing of the Package.

POTABLE WATER MAKER (UM-5121501A/B) the package name.

All definitions are found on I-ET-3010.00-1200-940-P4X-002 — GENERAL TECHNICAL TERMS

1.3. ABBREVIATIONS

CCR Central Control Room

CS Classification Society

FAT Factory Acceptance Tests

FPSO Floating Production Storage and Offloading Unit

SOS......Supervisory and Operation System

SOS-HMI..... Human Machine Interface of SOS

2. NORMATIVE REFERENCES

2.1. INTERNATIONAL CODES, RECOMMENDED PRACTICES AND STANDARDS

The equipment will be designed and manufactured in accordance with the following codes and standards, if not mentioned otherwise.

- ANSI American National Standards Institute
- API American Petroleum Institute
- ASME American Society Of Mechanical Engineers
- BGV German Safety Regulations
- DIN German National Standard Code

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-I	P4X-002	REV.	Α
BR	BÚZIOS	S	SHEET: 5	of	21
PETROBRAS	POTABLE WATI	ER MAKER SYSTEM	INTERNAL		
	(UM-5121	501 A/B)	ESU	Р	

- EN European Standards
- ISO International Standard Organization
- IMO International Maritime Organization
- MARPOL Chapter IV
- VDE / IEC German National Electric Standard Codes / International
- Electric Codes
- Classification Society defined for the Hull scope.

2.2. BRAZILIAN CODES AND STANDARDS

- NR Brazilian Federal Government Regulatory Norms (Normas Regulamentadoras NRs)
- NORMAM-01 Normas da Autoridade Marítima para Embarcações Empregadas na Navegação em Mar Aberto;
- Brazilian Government Ministry of Healthy Regulation "PORTARIA DE CONSOLIDAÇÃO № 5, DE 28 DE SETEMBRO DE 2017", Anexo XX. "Consolidation Ordinance No. 5 of the Ministry of Health, 28th September 2017 on Annex XX".
- ANVISA RDC 72/2009.

2.3. CLASS APPROVAL AND CERTIFICATION

The PACKAGE shall be designed, manufactured and tested according to the design reference documents, normative requirements and in accordance with the latest editions of Classification Society Rules, Regulations and Standards.

3. REFERENCE DOCUMENTS

REF DOC NUMBER	REF DOC NAME
GENERAL	
I-DE-3010.1Y-1200-942-P4X-001	GENERAL ARRANGEMENT
I-DE-3010.1Y-5400-94A-P4X-001	AREA CLASSIFICATION – GENERAL
I-ET-3000.00-0000-940-P4X-002	SYMBOLS FOR PRODUCTION UNITS DESIGN
I-ET-3000.00-1200-940-P4X-001	TAGGING PROCEDURE FOR PRODUCTION UNITS DESIGN



TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-I		REV.	Α
BÚZIOS		sheet: 6	of	21
POTABLE WATER MAKER SYSTEM		INTERNAL		
(UM-5121	I501 A/B)	ESU	Р	

I-RL-3010.1Y-1200-940-P4X-001 GENERAL SPECIFICATION FOR AVAILABLE UTILITIES I-ET-3A36.00-1000-941-PPC-001 METOCEAN DATA I-ET-3010.00-1200-955-P4X-001 WELDING I-ET-3010.00-1000-970-P4X-002 REQUIREMENTS FOR NDT I-ET-3010.00-1200-955-P4X-002 REQUIREMENTS FOR WELDING I-ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR WELDING I-ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR PROCEDURES AND PERSONNEL QUALIFICATION AND CERTIFICATION I-DE-3010.1Y-5115-944-P4X-002 FRESH, HOT AND POTABLE WATER SYSTEM I-DE-3010.1Y-5115-944-P4X-003 FRESH, HOT AND POTABLE WATER SYSTEM DISTRIBUTION I-MD-3010.1Y-1200-940-P4X-027 DESCRIPTIVE MEMORANDUM - HULL SYSTEMS NAVAL I-ET-3010.1Y-1350-960-P4X-002 DESIGN REQUIREMENTS - NAVAL ARCHITECTURE I-RL-3010.1Y-1350-960-P4X-009 MOTION ANALYSIS MECHANICAL I-ET-3010.00-1200-300-P4X-001 REQUIREMENTS PAINTING I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING DR-ENGP-I-1.15 COLOR CODING SAFFTY		
CONSTRUCTION FET-3010.00-1200-955-P4X-001 WELDING -ET-3010.00-1000-970-P4X-002 REQUIREMENTS FOR NDT -ET-3010.00-1200-955-P4X-002 REQUIREMENTS FOR WELDING -ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR WELDING -ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR PROCEDURES AND PERSONNEL -ET-3010.01Y-5115-944-P4X-002 FRESH, HOT AND POTABLE WATER SYSTEM -DE-3010.1Y-5115-944-P4X-003 FRESH, HOT AND POTABLE WATER SYSTEM DISTRIBUTION -MD-3010.1Y-1200-940-P4X-027 DESCRIPTIVE MEMORANDUM - HULL SYSTEMS -ET-3010.1Y-1350-960-P4X-002 DESIGN REQUIREMENTS - NAVAL -ET-3010.1Y-1350-960-P4X-009 MOTION ANALYSIS -ET-3010.00-1200-300-P4X-001 NOISE AND VIBRATION CONTROL REQUIREMENTS -ET-3010.00-1200-956-P4X-002 GENERAL PAINTING	I-RL-3010.1Y-1200-940-P4X-001	
-ET-3010.00-1200-955-P4X-001 WELDING -ET-3010.00-1000-970-P4X-002 REQUIREMENTS FOR NDT -ET-3010.00-1200-955-P4X-002 REQUIREMENTS FOR WELDING INSPECTION -ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR WELDING INSPECTION -ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR PROCEDURES AND PERSONNEL QUALIFICATION AND CERTIFICATION	I-ET-3A36.00-1000-941-PPC-001	METOCEAN DATA
I-ET-3010.00-1000-970-P4X-002 REQUIREMENTS FOR NDT I-ET-3010.00-1200-955-P4X-002 REQUIREMENTS FOR WELDING INSPECTION I-ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR PROCEDURES AND PERSONNEL QUALIFICATION AND CERTIFICATION I-DE-3010.1Y-5115-944-P4X-002 FRESH, HOT AND POTABLE WATER SYSTEM I-DE-3010.1Y-5115-944-P4X-003 FRESH, HOT AND POTABLE WATER SYSTEM DISTRIBUTION I-MD-3010.1Y-1200-940-P4X-027 DESCRIPTIVE MEMORANDUM - HULL SYSTEMS I-ET-3010.1Y-1350-960-P4X-002 DESIGN REQUIREMENTS - NAVAL ARCHITECTURE I-RL-3010.1Y-1350-960-P4X-009 MOTION ANALYSIS MECHANICAL I-ET-3010.00-1200-300-P4X-001 NOISE AND VIBRATION CONTROL REQUIREMENTS I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING I-ET-3010.00-1200-956-P4X-00	CONSTRUCTION	
I-ET-3010.00-1200-955-P4X-002 REQUIREMENTS FOR WELDING INSPECTION I-ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR PROCEDURES AND PERSONNEL QUALIFICATION AND CERTIFICATION I-DE-3010.1Y-5115-944-P4X-002 FRESH, HOT AND POTABLE WATER SYSTEM I-DE-3010.1Y-5115-944-P4X-003 FRESH, HOT AND POTABLE WATER SYSTEM DISTRIBUTION I-MD-3010.1Y-1200-940-P4X-027 DESCRIPTIVE MEMORANDUM - HULL SYSTEMS I-ET-3010.1Y-1350-960-P4X-002 DESIGN REQUIREMENTS - NAVAL ARCHITECTURE I-ET-3010.00-1200-300-P4X-001 REQUIREMENTS I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING I-ET-3010.00-1200-956	I-ET-3010.00-1200-955-P4X-001	WELDING
INSPECTION	I-ET-3010.00-1000-970-P4X-002	REQUIREMENTS FOR NDT
I-ET-3010.00-0000-970-P4X-001	I-ET-3010.00-1200-955-P4X-002	·
I-DE-3010.1Y-5115-944-P4X-002	I-ET-3010.00-0000-970-P4X-001	PROCEDURES AND PERSONNEL QUALIFICATION AND
I-DE-3010.1Y-5115-944-P4X-002 SYSTEM	HULL SYSTEMS	
I-DE-3010.1Y-5115-944-P4X-003 SYSTEM DISTRIBUTION I-MD-3010.1Y-1200-940-P4X-027 DESCRIPTIVE MEMORANDUM - HULL SYSTEMS I-ET-3010.1Y-1350-960-P4X-002 DESIGN REQUIREMENTS - NAVAL ARCHITECTURE I-RL-3010.1Y-1350-960-P4X-009 MOTION ANALYSIS I-ET-3010.00-1200-300-P4X-001 NOISE AND VIBRATION CONTROL REQUIREMENTS I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING DR-ENGP-I-1.15 COLOR CODING	I-DE-3010.1Y-5115-944-P4X-002	·
NAVAL	I-DE-3010.1Y-5115-944-P4X-003	
I-ET-3010.1Y-1350-960-P4X-002 DESIGN REQUIREMENTS - NAVAL ARCHITECTURE I-RL-3010.1Y-1350-960-P4X-009 MOTION ANALYSIS MECHANICAL NOISE AND VIBRATION CONTROL REQUIREMENTS PAINTING I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING DR-ENGP-I-1.15 COLOR CODING	I-MD-3010.1Y-1200-940-P4X-027	
I-E1-3010.1Y-1350-960-P4X-002 ARCHITECTURE	NAVAL	
MECHANICAL I-ET-3010.00-1200-300-P4X-001 PAINTING I-ET-3010.00-1200-956-P4X-002 DR-ENGP-I-1.15 NOISE AND VIBRATION CONTROL REQUIREMENTS POINTING COLOR CODING	I-ET-3010.1Y-1350-960-P4X-002	
I-ET-3010.00-1200-300-P4X-001 NOISE AND VIBRATION CONTROL REQUIREMENTS PAINTING I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING DR-ENGP-I-1.15 COLOR CODING	I-RL-3010.1Y-1350-960-P4X-009	MOTION ANALYSIS
PAINTING I-ET-3010.00-1200-300-P4X-001 REQUIREMENTS PAINTING I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING DR-ENGP-I-1.15 COLOR CODING	MECHANICAL	
I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING DR-ENGP-I-1.15 COLOR CODING	I-ET-3010.00-1200-300-P4X-001	
DR-ENGP-I-1.15 COLOR CODING	PAINTING	
	I-ET-3010.00-1200-956-P4X-002	GENERAL PAINTING
SAFFTY	DR-ENGP-I-1.15	COLOR CODING
	SAFETY	



TECHNICAL SPECIFICATION	Nr: I-ET-3010.1Y-5121-600-	P4X-002	REV.	Α
BÚZIOS			of	21
POTABLE WATER MAKER SYSTEM		INTER	NAL	
(UM-5121501 A/B)			ID	

I-ET-3010.00-5400-947-P4X-002	SAFETY SIGNALING
DR-ENGP-M-I-1.3	SAFETY ENGINEERING GUIDELINE
PIPING	
I-ET-3010.1Y-1200-200-P4X-002	PIPING SPECIFICATION FOR HULL
I-ET-3010.00-1200-251-P4X-001	REQUIREMENTS FOR BOLT MATERIALS
ELECTRICAL	
I-DE-3010.00-5140-700-P4X-003	GROUNDING INSTALLATION TYPICAL DETAILS.
I-ET-3010.00-5140-700-P4X-003	ELECTRICAL REQUIREMENTS FOR PACKAGES FOR OFFSHORE UNITS
I-ET-3010.00-5140-712-P4X-001	LOW-VOLTAGE INDUCTION MOTORS FOR OFFSHORE UNITS
I-ET-3010.00-5140-700-P4X-002	SPECIFICATION FOR ELECTRICAL MATERIAL AND EQUIPMENT FOR OFFSHORE UNITS
INSTRUMENTATION AND AUTOM	ATION
I-ET-3010.00-1200-800-P4X-002	AUTOMATION, CONTROL AND INSTRUMENTATION ON PACKAGE UNITS
I-ET-3010.1Y-1200-800-P4X-014	AUTOMATION INTERFACE OF PACKAGE UNITS
I-ET-3010.00-1200-800-P4X-013	GENERAL CRITERIA FOR INSTRUMENTATION PROJECTS
I-ET-3010.00-5520-888-P4X-001	AUTOMATION PANELS
Table 1 – Re	ference Documents
te: Reference Documents latest revisi	on shall be considered

Note: Reference Documents latest revision shall be considered.

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	HEV.	Α
BR	BÚZIOS	3	SHEET: 8	of	21
PETROBRAS	POTABLE WATI	ER MAKER SYSTEM	INTERNAL		
	(UM-5121	501 A/B)	ESU	ΙP	

4. DESIGN REQUIREMENTS

4.1. DESIGN CONDITIONS

- 4.1.1. PACKAGE Equipment shall be designed for a 30-year life in a corrosive offshore environment without the need for replacement of any major component due to wear, corrosion, fatigue, or material failure.
- 4.1.2. PACKAGER shall design the equipment for the full range of operational conditions as specified in this technical specification.
- 4.1.3. PACKAGE Equipment shall be designed with the compliance of the normative and design requirements as stated in this specification and complying with the technical parameters stated on the above item 3 with the High Capacity FPSO basic design reference documents.
- 4.1.4. All elements of the PACKAGE shall be of proven design and well within the manufacturer's actual experience.

4.2. SAFETY REQUIREMENTS

- 4.2.1. Personnel safety protection shall be provided according to Brazilian Regulatory Norms (NR) issued by Brazilian Government.
- 4.2.2. Warning signs in Brazilian Portuguese language shall be provided where risk of personnel injury exist.
- 4.2.3. Rotating equipment outer parts, such as pulleys, couplings, belts and flywheels, shall have rigid protection, manufactured with aluminum ASTM B211 and shall be capable of being easily removed.
- 4.2.4. In accordance with the requirements of SOLAS II-1, Regulation 3-5, and MSC.1/Circ. 1379, all equipment and material to be supplied by PACKAGER must be "asbestos free".
- 4.2.5. Safety signaling shall be in full compliance with I-ET-3010.00-5400-947-P4X-002 SAFETY SIGNALING.
- 4.2.6. Double block & bleed arrangements are required for isolation of equipment in piping classes of 300# and above.

4.3. NOISE AND VIBRATIONS

4.3.1. Noise and vibrations limits shall be in conformance with I-ET-3010.00-1200-300-P4X-001 – NOISE AND VIBRATION CONTROL REQUIREMENTS.

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	REV.	Α
BR	BÚZIOS	3	SHEET: 9	of	21
PETROBRAS	POTABLE WATE	ER MAKER SYSTEM	INTERNA		
	(UM-5121	501 A/B)	ESU	Р	

4.4. MOTIONS AND ACCELERATION

- 4.4.1. All equipment shall be able to withstand with the UNIT subjected to 100-year return period environmental conditions.
- 4.4.2. All equipment shall be able to operate with the UNIT subjected to 1-year return period environmental conditions.
- 4.4.3. All environmental conditions are defined in I-ET-3A36.00-1000-941-PPC-001 METOCEAN DATA, at any draft from fully loaded to the minimum loaded / ballasted condition.
- 4.4.4. For the Hull loading conditions details and the maximum designed operational trim and heel inclinations refer to I-ET-3010.1Y-1350-960-P4X-002 DESIGN REQUIREMENTS NAVAL ARCHITECTURE.
- 4.4.5. For the design data and information regarding motion requirements refer to I-RL-3010.1Y-1350-960-P4X-009 MOTION ANALYSIS.
- 4.4.6. PACKAGE is also to withstand inertial forces during transportation from construction site to the final offshore location.

5. PACKAGE SCOPE OF SUPPLY

5.1. SCOPE OF SUPPLY

5.1.1. PACKAGER shall supply the following items:

	TAG	Description	Qty
1	UM-5121501A/B	POTABLE WATER MAKER	2x100%
2	FT-UM-5121501A/B	POTABLE WATER MAKER FILTER	2X100%
3	Z-5121501A/B	ULTRAVIOLET STERILIZER UNIT	2X100%
4	PN-Z-5121501A/B	ULTRAVIOLET STERILIZER CONTROL PANEL	2X100%

Table 2 – Scope of Supply

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	REV.	Α
BR	BÚZIOS	3	SHEET: 10	of	21
PETROBRAS	POTABLE WATE	POTABLE WATER MAKER SYSTEM		NAL	
	(UM-5121	501 A/B)	ESU	Р	

- 5.1.2. All Skid control valves shall also be included on the PACKAGER scope of supply.
- 5.1.3. PACKAGE logic for control and automation shall be designed and supplied by PACKAGER.
- 5.1.4. Additionally, PACKAGE scope of supply shall include any other item inside the limits of the skid as valves, instruments, interconnection piping, accessories, electrical and power devices and any other device to ensure the PACKAGE safe operation and under the design and operational limits defined by this Technical Specification.

5.2. EQUIPMENT LOCATION

- 5.2.1. POTABLE WATER MAKER SYSTEM (UM-5121501A/B) shall be installed in Engine Room a closed and non-classified compartment.
- 5.2.2. Potable Water Makers (UM-5121501A/B) and Ultraviolet Sterilizer Unit (Z-5121501A/B) shall be installed in separate skids.
- 5.2.3. Potable Water Makers (UM-5121501A/B) shall be installed downstream the Fresh Water Hydrophore Unit and upstream the Ultraviolet Sterilizer Unit (Z-5121501A/B).
- 5.2.4. For equipment location both I-DE-3010.1Y-1200-942-P4X-001 GENERAL ARRANGEMENT and I-DE-3010.1Y-5400-94A-P4X-001 AREA CLASSIFICATION GENERAL shall be considered.

6. PACKAGE SPECIFICATION

6.1. POTABLE WATER MAKER (UM-5121501 A/B) SKID

- 6.1.1. Two identical Potable Water Maker (UM-5121501A/B) shall be supplied in a configuration 2 x 100% and each of the equipment shall have capacity for 3.5 m³/h of water maker.
- 6.1.2. Each of the Mineralization Unit shall be able to operate with any of the Ultraviolet Sterilizer Unit (Z-5121501A/B).
- 6.1.3. POTABLE WATER MAKER Filter (FT-UM-5121501A/B) shall be designed according to the PACKAGER / MANUFACTURER standard.
- 6.1.4. Potable water parameters shall reach the quality standard of the regulation stated by the Brazilian Government Ministry of Health: "PORTARIA DE CONSOLIDAÇÃO № 5, DE 28 DE SETEMBRO DE 2017, Anexo XX" "Consolidation Ordinance No. 5 of the Ministry of Health, 28th September 2017 on Annex XX" and "RESOLUÇÃO № 72, DE 29 DE DEZEMBRO DE 2009" ANVISA RDC 72/2009.
- 6.1.5. Each Potable Water Maker (UM-5121501A/B) shall have a flange connection for equipment draining purpose.

6.2. ULTRAVIOLET STERILIZATION UNIT (Z-5121501 A/B) SKID

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	REV.
BR	BÚZIOS	6	SHEET: 11	of 21
PETROBRAS	POTABLE WATE	ER MAKER SYSTEM	INTERI	NAL
	(UM-5121	501 A/B)	ESU	Р

- 6.2.1. Sterilizer unit shall follow the UV sterilizing principle.
- 6.2.2. UV Sterilizer unit (Z-5121501 A/B) 2 x 100% shall have each the capacity for 3.5 m³/h.
- 6.2.3. Sterilizing Unit shall be provided with an Ultraviolet Sterilizer Control Panel (PN-Z-5121501) in accordance with PACKAGER / MANUFACTURER's standard. At least the following functions shall be provided:
 - i. Sterilizing process self control.
 - ii. UV lamps failure monitoring.
 - iii. UV lamps age monitoring.
- 6.2.4. Single block valves are used for the selection of each of equipment Potable Water Makers (UM-5121501A/B) and Ultraviolet Sterilizer Unit (Z-5121501A/B) are to be operational.
- 6.2.5. Potable water after Ultraviolet Sterilizer Unit (Z-5121501A/B) shall be destinated to Accommodation Distribution, to eye washing stations and sinks and to Calorifier Units (Z-5125501).
- 6.2.6. Each Ultraviolet Sterilizer Unit (Z-5121501A/B) shall have a flange connection for equipment draining purpose.

7. GENERAL REQUIREMENTS

7.1. ELECTRICAL REQUIREMENTS

- 7.1.1. All electrical equipment installed in hazardous areas (see Area Classification documentation) or installed outdoors and kept on during emergency condition (ESD) shall be certified according to IEC 61892, INMETRO Resolution 179, May 18th 2010 and INMETRO resolution 89, February 23rd 2012.
- 7.1.2. All electrical signal connections for external interconnection with the panel shall be clustered in junction boxes with at least IP-56 level of protection, located inside the panel and grouped according to the different types of signals involved.
- 7.1.3. Electrical equipment and material shall comply with requirements of I-ET-3010.00-5140-700-P4X-002 SPECIFICATION FOR ELECTRICAL MATERIAL AND EQUIPMENT FOR OFFSHORE UNITS.
- 7.1.4. Electrical induction motors shall comply with requirements of I-ET-3010.00-5140-712-P4X-001 LOW-VOLTAGE INDUCTION MOTORS FOR OFFSHORE UNITS.
- 7.1.5. Concerning electrical system voltages and quantity of feeders for motors, panels and auxiliaries, centrifugal pumps shall be fed according to definitions of I-ET-

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	24X-002	REV.	
BR	BÚZIOS	3	SHEET: 12	of 21	
PETROBRAS	POTABLE WATE	ER MAKER SYSTEM	INTERI	NAL	
	(UM-5121	501 A/B)	ESU	Р	

3010.00-5140-700-P4X-003 – ELECTRICAL REQUIREMENTS FOR PACKAGES FOR OFFSHORE UNITS.

- 7.1.6. Power lighting and grounding installations inside the package shall comply with requirements of I-ET-3010.00-5140-700-P4X-003 ELECTRICAL REQUIREMENTS FOR PACKAGES FOR OFFSHORE UNITS.
- 7.1.7. Grounding installations shall comply with I-ET-3010.00-5140-700-P4X-001 SPECIFICATION FOR ELECTRICAL DESIGN FOR OFFSHORE UNITS and I-DE-3010.00-5140-700-P4X-003 GROUNDING INSTALLATION TYPICAL DETAILS.

7.2. INSTRUMENTATION AND AUTOMATION REQUIREMENTS

- 7.2.1. PACKAGE shall be protected with all necessary instruments to operate safely, adequately and without interruption in a tropical marine environment.
- 7.2.2. The instrumentation and control design shall fulfill the requirements of the following technical specifications:
 - i. I-ET-3010.00-1200-800-P4X-002 AUTOMATION, CONTROL AND INSTRUMENTATION ON PACKAGE UNITS.
 - ii. I-ET-3010.00-1200-800-P4X-013 GENERAL CRITERIA FOR INSTRUMENTATION PROJECTS.
- 7.2.3. The minimum requirements for the adequate interfacing of the PACKAGE Automation and Instrumentation System with the UNIT are described on I-ET-3010.1Y-1200-800-P4X-014 AUTOMATION INTERFACE OF PACKAGE UNITS.
- 7.2.4. For the control and automation panels design requirements I-ET-3010.00-5520-888-P4X-001 AUTOMATION PANELS shall be considered.

7.3. PAINTING REQUIREMENTS

- 7.3.1. Painting and coating in accordance with I-ET-3010.00-1200-956-P4X-002 GENERAL PAINTING and DR-ENGP-I-1.15 COLOR CODING.
- 7.3.2. All components shall be delivered fully painted/coated, unless otherwise indicated on this specification.
- 7.3.3. The performed pre-treatment and complete coating shall be in accordance with the paint manufacturer's data sheets.

7.4. SKIDS LAYOUT AND FOUNDATION REQUIREMENTS

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	² 4X-002	REV.	Α
BR	BÚZIOS	3	SHEET: 13	of	21
PETROBRAS	POTABLE WATI	ER MAKER SYSTEM	INTER	NAL	
	(UM-5121	501 A/B)	ESU	Р	

- 7.4.1. PACKAGE equipment Potable Water Makers (UM-5121501A/B) and Ultraviolet Sterilizer Unit (Z-5121501A/B) shall be installed each one on separated and dedicated skids structure with the below following items to be fulfilled.
- 7.4.2. PACKAGE Skid shall be designed to withstand the design conditions mentioned on item 4.4 and to ensure the lifting conditions on manufacturing site and shipyard. Lifting lugs shall be provided according to PACKAGER lifting procedure.
- 7.4.3. Skid foundation structural steel components shall be designed and fabricated in accordance with AISC ASD.
- 7.4.4. The Skid main frame shall be all welded construction. Structural skid welds, including lifting facilities shall be continuous and shall comply with AWS D1.1 (structural welding code) and CS Rules.
- 7.4.5. Skid structure shall be designed to be welded to the supporting structure unless otherwise specified.
- 7.4.6. PACKAGE skid layout and arrangement shall be designed to provide sufficient access to pumps, instruments, equipment, and control panels so as to ease the operability and maintenance with safe conditions. Instruments and alves shall be installed on a suitable height to allow safe access for monitoring, operation, and maintenance.
- 7.4.7. All necessary maintenance davits, monorails, padeyes or trolleys shall be provided to ensure the safe and easy maintenance conditions.
- 7.4.8. Access ladders, platforms, gratings and any other access device shall be metallic type and designed according to PACKAGER / MANUFACTURER standard and to the industrial recognized international codes.
- 7.4.9. PACKAGE Equipment and components shall be located entirely within the skids / equipment base perimeter, including all equipment, piping, valves, electrical, instrumentation and controls.

7.5. NAMEPLATES AND TAG NUMBERING

7.5.1. PACKAGER / MANUFACTURER Equipment shall have nameplates in Brazilian Portuguese language, made of stainless steel AISI 316L, with 3 mm minimum

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	A A
BR	BÚZIOS	3	SHEET: 14	of 21
PETROBRAS	POTABLE WATE	ER MAKER SYSTEM	INTERI	NAL
	(UM-5121	501 A/B)	ESU	Р

thickness and fixed by stainless steel (AISI 316L) bolts or fasteners on visible and accessible location.

- 7.5.2. Tagging of all instruments, electrical, mechanical and piping items, including valves, shall be carried out.
- 7.5.3. Tags shall be supplied with the number and description in the Brazilian Portuguese Language, unless otherwise stated in the technical data sheets.
- 7.5.4. For TAG numbering refer to I-ET-3000.00-1200-940-P4X-001 TAGGING PROCEDURE FOR PRODUCTION UNITS DESIGN
- 7.5.5. For Instrumentation tagging the ISA –5.1 and N-1710 shall be followed.

8. PACKAGE MANUFACTURING


8.1. GENERAL

- 8.1.1. All materials and equipment supplied by PACKAGER / MANUFACTURER shall be brand new (not overhauled), field proven, free from defects and accepted by Owner and the Classification Society.
- 8.1.2. Materials and equipment shall be manufactured according to internationally recognized standards for the offshore oil drilling and production industries, and shall be in conformance with the Basic Design and Agreement specifications and requirements.
- 8.1.3. Field proven definition: Systems and equipment shall demonstrate satisfactory operation at least in 3 floating offshore installation units, operating under process conditions (pressure, flow, capacity and similar fluids) for a minimum of 24,000 hours. For rotating equipment, they must demonstrate operation with fluid, flow and discharge pressure similar to the design. Unproven designs or prototypes (including components) without offshore service will not be accepted.

8.2. QUALITY ASSURANCE AND CONTROL SYSTEM

- 8.2.1. PACKAGER shall submit his Quality Assurance / Quality Control handbook to HULL SUPPLIER for information.
- 8.2.2. Engineering, fabrication and manufacturing shall conform to good manufacturing practices. Quality system according to ISO 9001 in relevant extent shall be in place and implemented.

8.3. WELDING AND NDT



- 8.3.1. All equipment, structures and piping welds shall be performed according to the requirements described in the latest revision of I-ET-3010.00-1200-955-P4X-001 WELDING.
- 8.3.2. Welding shall be carried out with procedures and welders qualified in accordance with ASME Section IX. Welding shall not be performed before qualified welding procedures have been approved.
- 8.3.3. Intermittent fillet welds are not acceptable.
- 8.3.4. Welding inspection and NDTs shall be performed according to the requirements described in the latest revision of
 - o I-ET-3010.00-1000-970-P4X-002 REQUIREMENTS FOR NDT.
 - o I-ET-3010.00-1200-955-P4X-002 REQUIREMENTS FOR WELDING INSPECTION.
- 8.3.5. Qualification and Certification for procedures and personnel shall be in accordance with I-ET-3010.00-0000-970-P4X-001 REQUIREMENTS FOR PROCEDURES AND PERSONNEL QUALIFICATION AND CERTIFICATION.
- 8.3.6. Final NDTs, for acceptance purposes shall be carried out after completion of any post weld heat treatment (when applicable) and before the applications of painting, hydrostatic testing, etc.

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-I	² 4X-002	nLv.	Α
BR	BÚZIOS	3	SHEET: 16	of	21
PETROBRAS	POTABLE WATI	ER MAKER SYSTEM	INTERI	NAL	
	(UM-5121	501 A/B)	ESU	Р	


DEV

8.4. INSPECTION AND TESTS

- 8.4.1. PACKAGER / MANUFACTURER shall develop and implement an Inspection and Test Plan (ITP) containing hold points, review and witness points following the schedule of the PACKAGE inspections, tests and events accordingly.
- 8.4.2. PACKAGE inspection, tests and events shall be attended by the MANUFACTURER, PACKAGER, HULL SUPPLIER, CS and OWNER inspection team whenever necessary.
- 8.4.3. PACKAGE shall be tested according to the design codes, applicable industry standards, CS Rules and any other one requirement stated on this technical specification.
- 8.4.4. Unless waive by OWNER, the following PACKAGE inspections and checks shall be witnessed by OWNER inspector:
 - i. verification of equipment construction materials (vessels, heat exchangers, pumps, etc.) for conformity with the specification requirements;
 - ii. verification of piping, fittings and valves conform to specification of materials and fabrication;
 - iii. reports for all NDT performed on the pressure retaining parts (radiographic, dye penetrant, magnetic particles and ultrasonic inspection);
 - iv. approval of the relief valve settings and witness of their testing after setting;
 - v. review of Inspection and Test Records;
 - vi. visual check.
 - vii. Electrical tests as:
 - a MEGGER test for cables and electric motors;
 - all tests stated in the respective motors and power / control panel respective specifications.

8.5. FACTORY ACCEPTANCE TEST (FAT)

8.5.1. FAT is a set of functional and performance tests to be executed in any equipment, electrical, instrumentation and telecom panels or any other commissionable item carried out on the PACKAGER / MANUFACTURER factory or in specialized test



facilities, in order to demonstrate its compliance with the project specifications and allow its release to shipyard.

- 8.5.2. For Factory Acceptance Test (FAT) minimum scope requirements:
 - i. Pressure test (usually hydrostatic) test of all vessels, heat exchangers, tanks, pumps, pipes and valves.
 - Note: All piping systems and equipment shall be drained and dried after hydrostatic testing.
 - ii. Electrical continuity checks on all wiring and earthing.
 - iii. Functional checks on all instruments and valves.
 - iv. Alarms and Equipment Protection Tests.
 - v. All other equipment tests and factory checking to be carried out according to the FAT procedure approved by parts.
- 8.5.3. For Factory Acceptance Test (FAT) event invitation e reports:
 - OWNER, CS and HULL SUPPLIER shall be communicated about the FAT event following ITP and the fabrication schedule. FAT invitation schedule shall be negotiated during PACKAGE kick-off meeting on the detail design phase.
 - ii. PACKAGER shall issue the FAT procedure for all parts involved as OWNER, HULL SUPPLIER and CS, where applicable, and submit to them for approval.
 - iii. PACKAGER shall issue the FAT report with all test results and duly signed or stamped by all parts that witnessed the FAT and with the test reference documentation attached.
 - iv. Acceptance of FAT will not be considered as the final acceptance test of the PACKAGE.

8.6. PRE-COMMISSIONING AND COMMISSIONING


	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	REV.	Α
BR	BÚZIOS	6	SHEET: 18	of	21
PETROBRAS	POTABLE WATI	ER MAKER SYSTEM	INTER	NAL	
	(UM-5121	501 A/B)	ESU	IP	

- 8.6.1. PACKAGER / MANUFACTURER shall be required to provide any necessary support for installation, assembly, pre-commissioning and commissioning of the PACKAGE either at a shore based fabrication yard or onboard the FPSO.
- 8.6.2. PACKAGER / MANUFACTURER is responsible for assembly supervision of the PACKAGE equipment, including the assembly of components to be delivered loose (for example, some components of the pumps, like stuffing box, etc.).
- 8.6.3. Final acceptance will be on satisfactory completion of commissioning tests as specified by OWNER.

9. PACKAGE DELIVERY REQUIREMENTS

9.1. PRESERVATION, PACKING AND TRANSPORTATION

- 9.1.1. PACKAGER / MANUFACTURER shall ensure all the conditions and practices of preservation, packing and transportation are fulfilled and following the PACKAGE / Equipment specific and technical characteristics recommendations.
- 9.1.2. PACKAGER / MANUFACTURER shall submit to HULL SUPPLIER the PACKAGE preservation requirements and recommendations with all necessary



considerations for the PACKAGE equipment preservation during the UNIT whole design life.

- 9.1.3. Preservation and packing shall be proper for transportation and storage in a marine environment and protected against moisture and damage during transport, handling and lifting.
- 9.1.4. In any case, suitable preservation and protective measures shall be provided to prevent equipment deterioration prior to entering into service.
- 9.1.5. All packing shall be clearly marked for shipping, including lifting points, gross weight, dimensions and center of gravity.
- 9.1.6. All sea fastening and temporary supports used on the equipment for shipment shall be clearly identified.
- 9.1.7. PACKAGER / MANUFACTURER shall ensure that all loose valves, tubes and instruments are supplied with plastic caps.
- 9.1.8. PACKAGER / MANUFACTURER shall also ensure that all electric panels and motors will be supplied with Volatile Corrosion Inhibitor (VCI) impregnated plastic protection or similar, and external plug for space heater connection.
- 9.1.9. PACKAGER / MANUFACTURER shall provide clear and comprehensive instructions on the exterior of all packages advising the necessary warning notices for unpacking, handling and installing the equipment on arrival at destination.
- 9.1.10. The equipment shall be thoroughly cleaned internally and be free of all loose foreign materials.
 - i. The preparation shall make the equipment suitable for outdoor storage in a coastal tropical climate from the time of Shipment.
 - ii. If there is a risk of damage to valves and other appurtenances during transportation, they shall be disconnected and tagged. All components shall then be securely packed as above.
 - iii. Spare parts and tools to be packed separately and clearly marked "Spare Parts" and "Tools" respectively.

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	REV.	Α
BR	BÚZIOS	3	SHEET: 20	of	21
PETROBRAS	PETROBRAS TITLE: POTABLE WATER MAKER SYSTEM		INTERNAL		
	(UM-5121	501 A/B)	ESU	Р	

9.2. SPARE PARTS, CONSUMABLES AND TOOLS

- 9.2.1. All equipment / material consumable and spare parts recommended by PACKAGER / MANUFACTURER for the construction, testing, commissioning, preoperation and start-up phases.
- 9.2.2. All spare parts recommended or required by the CS: such spare parts will be delivered together with the relevant equipment.
- 9.2.3. All special tools required for construction, pre-commissioning, commissioning and all levels of maintenance and operation.
- 9.2.4. Spare parts list recommended by PACKAGER / MANUFACTURER for two years of operation.

9.3. DOCUMENTATION

9.3.1. Drawings and Weight Control

For Engineering Documentation minimum requirements:

- i. PACKAGER / MANUFACTURER design drawings shall show all necessary dimensions and details required for interface information and installation.
- ii. Clearances for maintenance shall be shown on the drawings.
- iii. Drawings and documents shall be clear and completely legible with all text in the English language.
- iv. Instruction manuals for operation and maintenance of the PACKAGE equipment shall be provided in Portuguese language.
- v. Drawings are only accepted when signed by PACKAGER as checked and approved. All revised editions of drawings or documents shall show the revisions clearly marked up, the issue date and PACKAGER's checked and approved signatures.
- vi. PACKAGER / MANUFACTURER shall produce a weight / center of gravity data sheet considering each PACKAGE component with the respective assembly dry and operational weight and CoG.
 - Note: Operational weight means the component dry weight added to the respective component fluid weight on operational condition.
- vii. PACKAGER shall send in advance all recommendations for PACKAGE installation, maintenance and commissioning.

9.3.2. Data Book

PACKAGER shall issue a PACKAGE / Equipment Data Book to be delivered to HULL SUPPLIER for approval. Data Book minimum content shall be as the following:

	TECHNICAL SPECIFICATION	I-ET-3010.1Y-5121-600-F	P4X-002	REV.
BR	BÚZIOS	3	SHEET: 21	of 21
PETROBRAS TITLE: POTABLE WATER MAKER SYSTEM		INTER	NAL	
	(UM-5121	501 A/B)	ESU	Р

- i. Certified drawings, data sheets, technical specifications, performance curves and calculation memorandum.
- ii. Construction, maintenance and operating manuals, instructions for preservation and commissioning, and all catalogs, including of the subsuppliers.
- iii. All certificates of materials and equipment, certificates of electrical cables and equipment to hazardous areas, all tests, destructive and non-destructive examinations, test reports (including FAT), certificates and reports of classification society, procedures for welding qualifications and welding processes.
- iv. The documentation requested by Brazilian law NR-13, subdivided for equipment (if applicable).
- v. The documentation requested by Brazilian law NR-10, subdivided for equipment (if applicable).

Data Book delivery standard and conditions including number of parts and sections, number of printed and electronic copies will be further defined by OWNER on detail design phase.

9.4. TRAINING

9.4.1. PACKAGER shall provide training to qualify OWNER technicians for operation and maintenance (install, dismantle, replace parts, make adjustment, etc.) of each equipment.